

View Online at <https://aerobasegroup.com/nsn/6625-00-933-1254>

Circuit Current For Which Designed:

Ac

Overall Length:

3.156 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.841 inches

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.841 inches

Overall Height:

2.370 inches

Overall Width:

2.365 inches

Mounting Hole Diameter:

0.164 inches

Scale Division Quantity:

30 single indicator 1st range 10 single indicator 2nd range

Furnished Items And Quantity:

Nut 2; washer 2

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Four hole/stud rectangular/square

Sensitivity Rating:

50.0 millivolts

Dial Scale Marking Color:

White single indicator all ranges

Accuracy In Percent:

-2.0/+2.0 at full scale single indicator all ranges

Meter Depth Behind Mounting Flange:

2.016 inches

Meter Body Diameter Behind Mounting Flange:

2.157 inches

Movement Type:

Moving iron vane

Background Color:

Black single indicator all ranges

Pointer Color:

White single indicator all ranges

Scale Marking:

Load; 0; 5; 1.0; volts; 0; 10; 20; 30; push for volts

Mounting Facility Type And Quantity:

4 screw and 4 unthreaded hole

Scale Graduation Type:

Linear single indicator all ranges

Features Provided:

External shunting and zero adjuster

Movement Suspension Method:

Taut band

Circuit Attachment Method And Quantity:

2 threaded stud

Material:

Plastic

Nuclear Hardness Critical Feature:

Nonhardened

Surface Treatment:

Paint

Style Designator:

Rectangular flush mtg

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A310a0