

View Online at <https://aerobasegroup.com/nsn/6625-00-933-3150>

**Circuit Current For Which Designed:**

Dc

**Dielectric Withstanding Voltage In Volts:**

1500.0

**Overall Length:**

1.531 inches

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

1.312 inches

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

1.312 inches

**Overall Height:**

1.750 inches

**Overall Width:**

1.750 inches

**Mounting Hole Diameter:**

0.140 inches

**Scale Division Quantity:**

50 single indicator single range

**Furnished Items And Quantity:**

Nuts 4; lockwasher 4

**Indicator Type:**

Dial w/pointer

**Installation Design:**

Panel

**Mounting Arrangement Style:**

Four hole/stud rectangular/square

**Dial Scale Marking Color:**

Black single indicator single range

**Accuracy In Percent:**

-3.0/+3.0 at full scale single indicator single range

**Meter Depth Behind Mounting Flange:**

1.125 inches

**Meter Body Diameter Behind Mounting Flange:**

1.510 inches

**Movement Type:**

Moving coil, permanent magnet

**Background Color:**

White single indicator single range

**Pointer Color:**

Black single indicator single range

**Power Source:**

External

**Mounting Facility Type And Quantity:**

4 screw and 4 unthreaded hole

**Scale Graduation Type:**

Linear single indicator single range

**Measurement Range:**

+0.0/+5000.0 volts, dc single indicator single range

**Movement Suspension Method:**

Jewel pivot base

**Circuit Attachment Method And Quantity:**

2 solder lug

**Special Features:**

Sealed; ruggedized

**Material:**

Steel

**Nuclear Hardness Critical Feature:**

Nonhardened

**Surface Treatment:**

Paint

**Special Test Features:**

Conform to mil-m-10304

**Style Designator:**

Rectangular flush mtg

**Fsc Application Data:**

Test set, elect. Equip.

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiiig:**

A310a0