

View Online at <https://aerobasegroup.com/nsn/6625-00-934-8732>

Current Type:

Ac

Frequency Rating:

Between 50.0 hertz and 1.0 kilohertz

Frequency Range Rating:

+0.010/+50.000 megahertz

Accessory Component Quantity:

1 and 1 and 1 and 1 and 1 and 1 and 1 and 1 and 1 and 1

Accessory Controlling Agency:

Jetds

Accessory Identifying Number:

Pp-977/urm-25d type no. And cg-409/ (3ft. 11 in.) type no. And cg-409/u(c0ft. T in.) type no. And cn-223/urm-25d type no. And cn-224/urm-25d type no. And cx-1363/u type no. And mx-1487/urm-25d type no. And sm-35/urm-25 type no. And ug-684a/u type no. And cn-530/urm-25d type no.

Joint Electronics Type Designation System Item Name:

Rf sig generator set

Joint Electronics Type Designation System Item Type Number:

An/urm-25h

Output Impedance Rating:

50.0 ohms

Voltage Rating:

Between 103.0 volts and 126.0 volts

Frequency Band Quantity:

8

Modulation Type:

Am

Accessory Component Name:

Power supply; cord; cord; attenuator, fixed; attenuator, fixed; test lead; adapter test; antenna simulator; adapter conn; attenuator, fixed

Calibration Accuracy Rating:

Porm 0.5 pct accuracy

Calibrated Signal Output Range:

Plus 0.1 to plus 100000 uv

Modulator Location:

Internal

Modulated Frequency Rating:

400.0 hertz and 1.0 kilohertz

Modulation Degree:

Between 0.0 percent and 50.0 percent

Phase:

Single

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T320-j