

View Online at <https://aerobasegroup.com/nsn/6625-00-935-1365>

Circuit Current For Which Designed:

Ac or dc

Dielectric Withstanding Voltage In Volts:

1000.0

Overall Length:

2.844 inches

Mounting Hole Diameter:

0.150 inches

Overall Diameter:

3.500 inches

Environmental Protection:

Cold resistant and heat resistant

Mounting Bolt Circle Diameter:

3.160 inches

Furnished Items And Quantity:

Mtg hdw 3

Indicator Type:

Vibrating reed

Installation Design:

Panel

Register Quantity:

1

Mounting Arrangement Style:

Three hole/stud bolt circle

Dial Scale Marking Color:

Black single indicator single range

Resonant Reed Quantity:

9

Accuracy In Percent:

-3.0/+3.0 at full scale single indicator single range

Unable To Decode:

Unable to decode or unable to decode

Meter Depth Behind Mounting Flange:

2.250 inches

Meter Body Diameter Behind Mounting Flange:

2.688 inches

Movement Type:

Vibrating reed

Background Color:

White single indicator single range

Power Source:

External

Mounting Facility Type And Quantity:

1 flange and 3 screw and 3 unthreaded hole

Measurement Range:

+380.0/+420.0 hertz single indicator single range

Circuit Attachment Method And Quantity:

2 solder stud

Special Features:

Ruggedized

Material:

Plastic phenol-formaldehyde

Nuclear Hardness Critical Feature:

Nonhardened

Surface Treatment:

Enamel

Style Designator:

Round flush mtg

Supplementary Features:

Reeds have high q characteristics

Fsc Application Data:

Test set, elect. Equip

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A310a0