

View Online at https://aerobasegroup.com/nsn/6625-00-935-1457

## **Overall Length:**

19.000 inches

### Wattage Rating In Watts:

125.0

#### **Overall Height:**

5.250 inches

#### **Overall Width:**

17.000 inches

#### **Current Type:**

Ac

### Frequency Rating:

Between 50.0 hertz and 60.0 hertz

### **Electrical Connection Type:**

Bnc

### Joint Electronics Type Designation System Item Name:

#### Counter, electronic, digital readout

Joint Electronics Type Designation System Item Type Number:

Td-875/p//u

## Internal Battery Accommodation:

Not included

## Voltage Rating:

115.0 volts or 230.0 volts

## **Output Frequency Rating:**

50.0 megahertz

### **Electrical Connection Quantity:**

2

### Mounting Method:

Bench

#### Measurement Type:

Frequency and ratio and period average

### Frequency Range:

+0.000010/+50.000000 megahertz multiple period and +0.000000/+50.000000 megahertz multiple period and +0.010000/+2.000000

megahertz multiple period and +0.000000/+1.000000 megahertz multiple period and +0.000000/+1.000000 megahertz multiple period

#### Accuracy Rating:

Porm 1 count! Porm 1 count of f1 and porm trigger error of f2! Porm 0.03 pct trigger error

# Gate Time:

10.0 seconds

# Sensitivity Rating:

F1 input 0.1 v rms into 5000 ohms! F2 input 1.0 v rms, 10 kc per v

# Ratio Display:

F1/f2 times period multiplier

# Period Range:

+1.0/+100.0



## Period Range Step Quantity:

7 decade steps

## Count Rate:

0.0 megahertz single period and 50.0 megahertz single period and 10.0 hertz multiple period and 50.0 megahertz multiple period

## Internal Calibration Feature:

Not included

#### Display Type:

Numeric readout tube

### **Display Digit Quantity:**

8

## Display Units Indicator:

Included

### **Display Positioned Decimal Point:**

Provided

### **Display Storage Facility:**

Included

#### **Remote Control Provisions:**

Not included

#### Solid State Feature:

Included

#### **Inclosure Material And Location:**

Steel case

## Inclosure Surface Treatment And Location:

Enamel case

## **Plug-in Units Provision:**

Included

### **Standard Frequency Output Feature:**

Included

# Frequency Accuracy/stability:

Porm 0.3 pct

## **Output Frequency Waveform:**

Sinusoidal

### **Frequency Output Amplitude:**

6.0 volts peak to peak

### Phase:

Single

### Shelf Life:

N/a

### Unit Of Measure:

---

### Demilitarization:

Yes - demil/mli

# Fiig:

T297-a