

View Online at <https://aerobasegroup.com/nsn/6625-00-938-6501>

Circuit Current For Which Designed:

Ac

Overall Length:

3.125 inches

Mounting Hole Diameter:

0.156 inches

Overall Diameter:

3.500 inches

Mounting Bolt Circle Diameter:

3.160 inches

Furnished Items And Quantity:

Nut 4; washer 4

Indicator Type:

Vibrating reed

Installation Design:

Panel

Register Quantity:

1

Mounting Arrangement Style:

Three hole/stud bolt circle

Dial Scale Marking Color:

Black single indicator single range

Resonant Reed Quantity:

9

Accuracy In Percent:

-1.0/+1.0 at full scale single indicator single range

Meter Depth Behind Mounting Flange:

2.125 inches

Meter Body Diameter Behind Mounting Flange:

2.800 inches

Movement Type:

Vibrating reed

Background Color:

White single indicator single range

Power Source:

External

Mounting Facility Type And Quantity:

3 unthreaded hole

Measurement Range:

+380.0/+420.0 hertz single indicator single range

Circuit Attachment Method And Quantity:

2 screw and 2 solder lug and 2 threaded stud

Operating Voltage Rating In Volts:

Between 95.0 ac and 135.0 ac

Special Markings:

Frequency at top of meter face and cycles at bottom; lines at 380, 390, 400, 410 and 420 hz

Material:

Plastic

Nuclear Hardness Critical Feature:

Nonhardened

Style Designator:

Round flush mtg

Supplementary Features:

Power consumption 6.5 w max

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A310a0