

View Online at <https://aerobasegroup.com/nsn/6625-00-938-8784>

Circuit Current For Which Designed:

Dc

Overall Length:

2.067 inches

Mounting Hole Diameter:

0.112 inches

Scale Division Quantity:

40 single indicator single range

Overall Diameter:

2.750 inches

Environmental Protection:

Cold resistant and heat resistant and humidity resistant and shock resistant and vibration resistant

Mounting Bolt Circle Diameter:

2.440 inches

Furnished Items And Quantity:

Nuts 3; lockwashers 3

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Three hole/stud bolt circle

Dial Scale Marking Color:

Black single indicator single range

Accuracy In Percent:

-2.0/+2.0 at full scale single indicator single range

Unable To Decode:

Unable to decode or unable to decode

Meter Depth Behind Mounting Flange:

1.405 inches

Meter Body Diameter Behind Mounting Flange:

2.210 inches

Movement Type:

Moving coil, permanent magnet

Background Color:

White single indicator single range

Pointer Color:

Black single indicator single range

Power Source:

External

Mounting Facility Type And Quantity:

3 screw and 3 unthreaded hole

Scale Graduation Type:

Linear single indicator single range

Measurement Range:

-10.0/+10.0 milliamperes, dc single indicator single range

Scale Selection Method:

Terminal

Features Provided:

Nonglare glass and zero adjuster

Movement Suspension Method:

Jewel pivot base

Circuit Attachment Method And Quantity:

2 screw and 2 solder lug

Special Features:

Ruggedized and sealed

Material:

Steel

Nuclear Hardness Critical Feature:

Nonhardened

Special Test Features:

Complys with mil-m-10304

Style Designator:

Round flush mtg

Fsc Application Data:

Test set electronic

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A310a0