

View Online at <https://aerobasegroup.com/nsn/6625-00-939-7520>

Circuit Current For Which Designed:

Ac

Scale Division Quantity:

75 single indicator 2nd range

End Application:

Spruance class dd (963), virginia class cgn (41), los angeles class ssn (688), oliver perry class ffg, sturgeon class ssn (637), ticonderoga class cg (47), nimitz class cvn, forrestal class cv, kidd class ddg

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Sensitivity Rating:

1.0 milliamperes

Dial Scale Marking Color:

Black single indicator all ranges

Meter Body Diameter Behind Mounting Flange:

2.40625 inches

Movement Type:

Moving coil, permanent magnet

Background Color:

White single indicator all ranges

Pointer Color:

Black single indicator all ranges

Mounting Facility Type And Quantity:

4 unthreaded hole

Scale Graduation Type:

Nonlinear single indicator 3rd range

Measurement Range:

+0.0 to 15.0 amperes, ac single indicator 2nd range

Scale Selection Method:

Switch

Features Provided:

Zero adjuster

Movement Suspension Method:

Taut band

Circuit Attachment Method And Quantity:

2 turret

Material:

Plastic

Style Designator:

Rectangular flush mtg

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A310a0