

View Online at <https://aerobasegroup.com/nsn/6625-00-941-5855>

**Circuit Current For Which Designed:**

Dc

**Overall Length:**

2.820 inches

**Mounting Hole Diameter:**

0.150 inches

**Scale Division Quantity:**

30 single indicator all ranges

**Overall Diameter:**

3.510 inches

**Environmental Protection:**

Shock resistant and vibration resistant

**Mounting Bolt Circle Diameter:**

3.160 inches

**Furnished Items And Quantity:**

Mtg hdw 3

**Indicator Type:**

Dial w/pointer

**Installation Design:**

Panel

**Mounting Arrangement Style:**

Three hole/stud bolt circle

**Sensitivity Rating:**

1.0 milliamperes

**Dial Scale Marking Color:**

Black single indicator all ranges

**Accuracy In Percent:**

-2.0/+2.0 at full scale single indicator all ranges

**Meter Depth Behind Mounting Flange:**

1.500 inches

**Meter Body Diameter Behind Mounting Flange:**

2.800 inches

**Movement Type:**

Moving coil, permanent magnet

**Background Color:**

White single indicator all ranges

**Pointer Color:**

Black single indicator all ranges

**Power Source:**

External

**Mounting Facility Type And Quantity:**

3 screw and 3 unthreaded hole

**Scale Graduation Type:**

Linear single indicator all ranges

**Measurement Range:**

+0.0/+6.0 milliwatts single indicator 1st range

**Scale Selection Method:**

Terminal

**Features Provided:**

Zero adjuster

**Movement Suspension Method:**

Jewel pivot base

**Circuit Attachment Method And Quantity:**

2 solder lug

**Special Features:**

Ruggedized

**Special Markings:**

Drive pwr mw (above scale); radiate power mw (for upper range); bolometer input mw (lower range)

**Material:**

Steel

**Nuclear Hardness Critical Feature:**

Nonhardened

**Surface Treatment:**

Enamel

**Special Test Features:**

Sealed and ruggedized in accordance w/mil-m-10304

**Style Designator:**

Round flush mtg

**Supplementary Features:**

150 mv power consumption

**Fsc Application Data:**

Test set, elect. Equip.

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A310a0