## NSN 6625-00-941-5855

Wattmeter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6625-00-941-5855

Circuit Current For Which Designed:
Dc
Overall Length:
2.820 inches
Mounting Hole Diameter:
0.150 inches
Scale Division Quantity:
30 single indicator all ranges
Overall Diameter:
3.510 inches
Environmental Protection:
Shock resistant and vibration resistant
Mounting Bolt Circle Diameter:
3.160 inches
Furnished Items And Quantity:
Mtg hdw 3
Indicator Type:
Dial w/pointer
Installation Design:
Panel
Mounting Arrangement Style:
Three hole/stud bolt circle
Sensitivity Rating:
1.0 milliamperes
Dial Scale Marking Color:
Black single indicator all ranges
Accuracy In Percent:
-2.0/+2.0 at full scale single indicator all ranges
Meter Depth Behind Mounting Flange:
1.500 inches
Meter Body Diameter Behind Mounting Flange:
2.800 inches
Movement Type:
Moving coil, permanent magnet
Background Color:
White single indicator all ranges
Pointer Color:
Black single indicator all ranges
Power Source:
External
Mounting Facility Type And Quantity:
÷ • • •

3 screw and 3 unthreaded hole

## **NSN 6625-00-941-5855** Wattmeter - Page 2 of 2



Scale Graduation Type:	
Linear single indicator all ranges	
Measurement Range:	
+0.0/+6.0 milliwatts single indicator 1st range	
Scale Selection Method:	
Terminal	
Features Provided:	
Zero adjuster	
Movement Suspension Method:	
Jewel pivot base	
Circuit Attachment Method And Quantity:	
2 solder lug	
Special Features:	
Ruggedized	
Special Markings:	
Drive pwr mw (above scale); radiate power mw (for upper range); bolometer input mw (lower range)	
Material:	
Steel	
Nuclear Hardness Critical Feature:	
Nonhardened	
Surface Treatment:	
Enamel	
Special Test Features:	
Sealed and ruggedized in accordance w/mil-m-10304	
Style Designator:	
Round flush mtg	
Supplementary Features:	
150 mv power consumption	
Fsc Application Data:	
Test set, elect. Equip.	
Shelf Life:	
N/a	
Unit Of Measure:	
Demilitarization:	
No	
Fiig:	
A310a0	