## NSN 6625-00-941-6246

Power Factor Meter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6625-00-941-6246

Circuit Current For Which Designed:
Dc
Dielectric Withstanding Voltage In Volts:
1500.0
Overall Length:
2.001 inches
Mounting Hole Diameter:
0.120 inches
Scale Division Quantity:
4 single indicator single range
Overall Diameter:
2.500 inches
Environmental Protection:
Airtight and dust resistant and fungus resistant and heat resistant and humidity resistant and shock resistant and vibration resistant and
water resistant
Mounting Bolt Circle Diameter:
2.440 inches
Furnished Items And Quantity:
Shunt wire 1; nut 3; lockwasher 3; seal 2
Indicator Type:
Dial w/pointer
Installation Design:
Panel
Mounting Arrangement Style:
Three hole/stud bolt circle
Sensitivity Rating:
200.0 microamperes
Dial Scale Marking Color:
Black single indicator single range
Accuracy In Percent:
-2.0/+2.0 at full scale single indicator single range
Meter Depth Behind Mounting Flange:
1.081 inches
Meter Body Diameter Behind Mounting Flange:
2.150 inches
Movement Type:
Moving coil, permanent magnet
Background Color:
White single indicator single range
Pointer Color:

3 screw and 3 unthreaded hole

Black single indicator single range

**Mounting Facility Type And Quantity:** 

## NSN 6625-00-941-6246

Power Factor Meter - Page 2 of 2



Scale Graduation Type:
Linear single indicator single range
Measurement Range:
-10.0/+10.0 percent deviation single indicator single range
Scale Selection Method:
Terminal
Features Provided:
External shunting and zero adjuster
Movement Suspension Method:
Jewel pivot base
Circuit Attachment Method And Quantity:
2 solder lug
Special Features:
Ruggedized
Special Markings:
On front, off; set; on back, sealed do not open
Material:
Steel
Nuclear Hardness Critical Feature:
Nonhardened
Surface Treatment:
Enamel
Special Test Features:
Complies with mil-m-10304
Style Designator:
Round flush mtg
Fsc Application Data:
Test set, elect. Equip.
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A310a0