

View Online at <https://aerobasegroup.com/nsn/6625-00-945-0302>

Circuit Current For Which Designed:

Dc

Overall Length:

3.500 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

Between 3.361 inches and 3.391 inches

Center To Center Distance Between Mounting Facilities Parallel To Width:

Between 3.361 inches and 3.391 inches

Overall Height:

Between 4.250 inches and 4.750 inches

Overall Width:

Between 4.250 inches and 4.750 inches

Scale Division Quantity:

80 single indicator single range

Mounting Stud Length:

1.500 inches

Environmental Protection:

Shock resistant

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Four hole/stud rectangular/square

Sensitivity Rating:

100.0 millivolts

Dial Scale Marking Color:

Black single indicator single range

Accuracy In Percent:

-1.5/+1.5 at full scale single indicator single range

Meter Depth Behind Mounting Flange:

2.813 inches

Meter Body Diameter Behind Mounting Flange:

3.980 inches

Movement Type:

Moving coil, permanent magnet

Background Color:

White single indicator single range

Pointer Color:

Black single indicator single range

Mounting Facility Type And Quantity:

4 threaded stud

Scale Graduation Type:

Linear single indicator single range

Measurement Range:

-160.0/+160.0 amperes, dc single indicator single range

Mounting Stud Diameter:

0.250 inches

Features Provided:

Zero adjuster

Movement Suspension Method:

Taut band

Circuit Attachment Method And Quantity:

2 threaded stud

Material:

Plastic

Nuclear Hardness Critical Feature:

Nonhardened

Style Designator:

Rectangular flush mtg

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A310a0