NSN 6625-00-945-6740

Special Scale Meter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6625-00-945-6740

| Circuit Current For Which Designed: |
|---|
| Dc |
| Overall Length: |
| 2.000 inches |
| Mounting Hole Diameter: |
| Between 0.120 inches and 0.130 inches |
| Overall Diameter: |
| 2.695 inches |
| Mounting Bolt Circle Diameter: |
| Between 2.430 inches and 2.450 inches |
| Indicator Type: |
| Dial w/pointer |
| Installation Design: |
| Panel |
| Mounting Arrangement Style: |
| Three hole/stud bolt circle |
| Dial Scale Marking Color: |
| Black, federal standard 595, 27038 single indicator single range and blue single indicator single range and green single indicator single |
| range |
| Accuracy In Percent: |
| -2.0/+2.0 at full scale single indicator single range |
| Meter Depth Behind Mounting Flange: |
| 1.280 inches |
| Meter Body Diameter Behind Mounting Flange: |
| Between 2.140 inches and 2.160 inches |
| Movement Type: |
| Moving coil, permanent magnet |
| Background Color: |
| White single indicator single range |
| Pointer Color: |
| Black single indicator single range |
| Scale Marking: |
| Meter test; tracker alarm and system test |
| Mounting Facility Type And Quantity: |
| 3 unthreaded hole |
| Scale Graduation Type: |
| Nonlinear single indicator single range |
| Features Provided: |
| Zero adjuster |
| Movement Suspension Method: |

2 turret

Jewel pivot base

Circuit Attachment Method And Quantity:

NSN 6625-00-945-6740

Special Scale Meter - Page 2 of 2



| Material: |
|-------------------------------------|
| Steel |
| Nuclear Hardness Critical Feature: |
| Nonhardened |
| Style Designator: |
| Round flush mtg |
| Supplementary Features: |
| Resistance 3600 ohms porm 1500 ohms |
| Fsc Application Data: |
| Test set, elect. Equip. |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |

A310a0