

View Online at <https://aerobasegroup.com/nsn/6625-00-945-9371>

Circuit Current For Which Designed:

Dc

Overall Length:

2.030 inches

Scale Division Quantity:

4 single indicator single range

Mounting Stud Length:

0.562 inches

Overall Diameter:

2.280 inches

Distance Between Mounting Facility Centers:

1.750 inches

Furnished Items And Quantity:

Nut 4; washer 4

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Two hole/stud

Sensitivity Rating:

60.0 amperes

Dial Scale Marking Color:

White single indicator single range

Accuracy In Percent:

-2.0/+2.0 at 1/4 scale single indicator single range

Meter Depth Behind Mounting Flange:

1.810 inches

Meter Body Diameter Behind Mounting Flange:

1.940 inches

Movement Type:

Moving iron vane

Background Color:

Black single indicator single range

Pointer Color:

White single indicator single range

Power Source:

External

Mounting Facility Type And Quantity:

1 clamp and 2 threaded stud

Scale Graduation Type:

Linear single indicator single range

Measurement Range:

-60.0/+60.0 amperes, dc single indicator single range

Mounting Stud Diameter:

0.219 inches

Features Provided:

Self-illumination facility

Movement Suspension Method:

Taut band

Circuit Attachment Method And Quantity:

2 threaded stud

Material:

Steel

Nuclear Hardness Critical Feature:

Nonhardened

Style Designator:

Round flush mtg

Supplementary Features:

Battery and generator terminal leads to be reversed for pos ground system

Fsc Application Data:

Test set, electronic equipment

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A310a0