

View Online at <https://aerobasegroup.com/nsn/6625-00-946-1486>

Circuit Current For Which Designed:

Ac

Overall Length:

19.000 inches

Overall Height:

10.469 inches

Overall Width:

13.875 inches

Scale Division Quantity:

1 single indicator single range

Frequency Rating:

Between 50.0 hertz and 60.0 hertz

Furnished Items And Quantity:

Cable assembly pn 340a-16a

Indicator Type:

Dial w/pointer

Installation Design:

Rack

Frequency Response Range:

+30.000 to 60.000 megahertz

Dial Scale Marking Color:

Black single indicator single range

Accuracy In Percent:

-1.0 to 1.0 at full scale single indicator single range

Background Color:

White single indicator single range

Pointer Color:

Black single indicator single range

Power Source:

External

Scale Graduation Type:

Linear single indicator single range

Measurement Range:

+0.0 to 30.0 decibels single indicator single range

Scale Selection Method:

Switch

Circuit Attachment Method And Quantity:

2 connector, receptacle

Operating Voltage Rating In Volts:

115.0 ac and 230.0 ac

Phase:

Single

Special Features:

Input impedance: 50 ohms ; bandwidth: 1.0 mhz min.; agc output: 0 to minus 6v from rear binding posts

Functional Description:

Measures noise figure in microwave or radar receivers, rf and if amplifiers; compares unknown noise sources to known noise levels

Reference Data And Literature:

Hp 1972 catalog

Style Designator:

D1 rectangular or square

Supplementary Features:

Opt r: rack

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A310a0