

View Online at <https://aerobasegroup.com/nsn/6625-00-948-0077>

Width:

11.400 inches

Length:

13.700 inches

Ac Voltage Rating:

115.0 volts

Dc Voltage Rating:

28.0 volts

Frequency Rating:

Between 50.0 hertz and 420.0 hertz

Major Components:

5attenuator, fixed; cable assembly, power, electrical; cable assembly, power, electrical; cable assembly, power; cable assembly, radio frequency; cable assembly, radio frequency; cover, test set; shoulder strap, test set; test hood, antenna; test set, transponder set

Accessory Component Quantity:

1 and 1 and 1 and 1 and 1 and 1 and 1 and 1 and 1 and 1

Accessory Controlling Agency:

Jetds and jetds and jetds and jetds and jetds and jetds and jetds and jetds and jetds and jetds

Accessory Identifying Number:

Cn-1088/u type no. And cx-11626/apm-123/v/ type no. And cx-11627/apm-123/v/ type no. And cx-11628/apm-123 type no. And cg-409g/u/25 ft type no. And cg-3308/u/6 in. Type no. And cw-890/apm-123/v/ type no. And mx-7344/apm-123/v/ type no. And mx-4396/apm-123/v/ type no. And ts-1809/apm-123/v/ type no.

Joint Electronics Type Designation System Item Name:

Test set, transponder set

Joint Electronics Type Designation System Item Type Number:

Type no. An/apm-123/v/2

Internal Battery Accommodation:

Not included

Material And Location:

Aluminum carrying case

Inclosure Feature:

Single item w/carrying case

Test Type For Which Designed:

Receiver frequency reply code selectivity side lobe suppression transmitter frequency transmitter power output

Operating Test Capability:

Receiver 1090 mc, porm 3 mc, freq minus 6 dbm to minus 12 dbm nom sensitivity transmitter 1030 mc, porm 0.02 pct, freq minus 6 dbm to minus 12 dbm power output

Phase:

Single

Height:

11.100 inches

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Fig:

T228-a