

View Online at <https://aerobasegroup.com/nsn/6625-00-948-0077>

**Width:**

11.400 inches

**Length:**

13.700 inches

**Ac Voltage Rating:**

115.0 volts

**Dc Voltage Rating:**

28.0 volts

**Frequency Rating:**

Between 50.0 hertz and 420.0 hertz

**Major Components:**

5attenuator, fixed; cable assembly, power, electrical; cable assembly, power, electrical; cable assembly, power; cable assembly, radio frequency; cable assembly, radio frequency; cover, test set; shoulder strap, test set; test hood, antenna; test set, transponder set

**Accessory Component Quantity:**

1 and 1 and 1 and 1 and 1 and 1 and 1 and 1 and 1 and 1

**Accessory Controlling Agency:**

Jetds and jetds and jetds and jetds and jetds and jetds and jetds and jetds and jetds and jetds

**Accessory Identifying Number:**

Cn-1088/u type no. And cx-11626/apm-123/v/ type no. And cx-11627/apm-123/v/ type no. And cx-11628/apm-123 type no. And cg-409g/u/25 ft type no. And cg-3308/u/6 in. Type no. And cw-890/apm-123/v/ type no. And mx-7344/apm-123/v/ type no. And mx-4396/apm-123/v/ type no. And ts-1809/apm-123/v/ type no.

**Joint Electronics Type Designation System Item Name:**

Test set, transponder set

**Joint Electronics Type Designation System Item Type Number:**

Type no. An/apm-123/v/2

**Internal Battery Accommodation:**

Not included

**Material And Location:**

Aluminum carrying case

**Inclosure Feature:**

Single item w/carrying case

**Test Type For Which Designed:**

Receiver frequency reply code selectivity side lobe suppression transmitter frequency transmitter power output

**Operating Test Capability:**

Receiver 1090 mc, porm 3 mc, freq minus 6 dbm to minus 12 dbm nom sensitivity transmitter 1030 mc, porm 0.02 pct, freq minus 6 dbm to minus 12 dbm power output

**Phase:**

Single

**Height:**

11.100 inches

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

**Fig:**

T228-a