NSN 6625-00-950-6359

Arbitrary Scale Meter - Page 1 of 2

Circuit Current For Which Designed:



View Online at https://aerobasegroup.com/nsn/6625-00-950-6359

Dielectric Withstanding Voltage In Volts:
3000.0
Overall Length:
2.650 inches
Mounting Hole Diameter:
Between 0.120 inches and 0.130 inches
Overall Diameter:
2.695 inches
Environmental Protection:
Shock resistant and vibration resistant
Mounting Bolt Circle Diameter:
2.440 inches
Furnished Items And Quantity:
Mtg hdw 3
Indicator Type:
Dial w/pointer
Installation Design:
Panel
Mounting Arrangement Style:
Three hole/stud bolt circle
Sensitivity Rating:
50.0 microamperes
Dial Scale Marking Color:
White single indicator single range
Accuracy In Percent:
-2.0/+2.0 at full scale single indicator single range
Unable To Decode:
Unable to decode or unable to decode
Meter Depth Behind Mounting Flange:
1.600 inches
Meter Body Diameter Behind Mounting Flange:
2.210 inches
Movement Type:
Moving coil, permanent magnet
Background Color:
Black single indicator single range
Pointer Color:
White single indicator single range
Scale Marking:
Good; red zones

NSN 6625-00-950-6359Arbitrary Scale Meter - Page 2 of 2



Mounting Facility Type And Quantity:
3 unthreaded hole
Scale Graduation Type:
Nonlinear single indicator single range
Features Provided:
Magnetic shield and zero adjuster
Movement Suspension Method:
Jewel pivot base
Circuit Attachment Method And Quantity:
2 solder lug and 2 threaded stud
Special Features:
Ruggedized
Special Markings:
Red band from 0 to 35 ua and from 45 to 50 ua deflection points
Material:
Steel
Nuclear Hardness Critical Feature:
Nonhardened
Surface Treatment:
Enamel semigloss
Style Designator:
Round flush mtg
Fsc Application Data:
Test set, elect. Equip.
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A310a0