

View Online at <https://aerobasegroup.com/nsn/6625-00-951-0932>

**Circuit Current For Which Designed:**

Ac

**Overall Length:**

11.000 inches

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

3.375 inches

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

3.375 inches

**Overall Height:**

Between 4.250 inches and 4.750 inches

**Overall Width:**

Between 4.250 inches and 4.750 inches

**Scale Division Quantity:**

30 single indicator single range

**Mounting Stud Length:**

Between 0.500 inches and 0.750 inches

**Installation Design:**

Panel

**Mounting Arrangement Style:**

Four hole/stud rectangular/square

**Frequency Response Range:**

+54.000/+66.000 hertz

**Dial Scale Marking Color:**

Black single indicator single range

**Accuracy In Percent:**

-1.5/+1.5 at full scale single indicator all ranges

**Meter Depth Behind Mounting Flange:**

10.000 inches

**Meter Body Diameter Behind Mounting Flange:**

3.980 inches

**Movement Type:**

Moving iron vane

**Background Color:**

White single indicator single range

**Mounting Facility Type And Quantity:**

4 threaded stud

**Measurement Range:**

+0.0/+150.0 volts, ac single indicator single range

**Mounting Stud Diameter:**

0.250 inches

**Features Provided:**

Magnetic shield

**Circuit Attachment Method And Quantity:**

2 threaded stud

**Material:**

Plastic

**Style Designator:**

Rectangular flush mtg

**Test Data Document:**

81349-mil-16034 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fig:**

A310a0