

View Online at <https://aerobasegroup.com/nsn/6625-00-951-4581>

Circuit Current For Which Designed:

Ac

Dielectric Withstanding Voltage In Volts:

3000.0

Overall Length:

2.922 inches

Mounting Hole Diameter:

0.125 inches

Scale Division Quantity:

4 single indicator single range

Frequency Rating:

400.0 hertz

Overall Diameter:

2.703 inches

Environmental Protection:

Shock resistant and vibration resistant

Mounting Bolt Circle Diameter:

2.440 inches

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Three hole/stud bolt circle

Frequency Response Range:

+380.000/+420.000 hertz

Sensitivity Rating:

1.0 watts

Dial Scale Marking Color:

Black single indicator single range

Accuracy In Percent:

-0.5/+0.5 at full scale single indicator single range

Unable To Decode:

Unable to decode or unable to decode

Meter Depth Behind Mounting Flange:

2.438 inches

Meter Body Diameter Behind Mounting Flange:

2.156 inches

Movement Type:

Moving iron vane

Background Color:

White single indicator single range

Pointer Color:

Black single indicator single range

Power Source:

External

Mounting Facility Type And Quantity:

3 unthreaded hole

Scale Graduation Type:

Linear single indicator single range

Measurement Range:

+110.0/+130.0 volts, ac single indicator single range

Scale Selection Method:

Terminal

Features Provided:

Zero adjuster

Movement Suspension Method:

Taut band

Circuit Attachment Method And Quantity:

2 solder lug

Operating Voltage Rating In Volts:

120.0 ac

Phase:

Single

Special Features:

Ruggedized

Special Markings:

Broad band on range

Material:

Steel

Nuclear Hardness Critical Feature:

Nonhardened

Surface Treatment:

Enamel

Style Designator:

Round flush mtg

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiiig:

A310a0