NSN 6625-00-953-4644

Electrical Frequency Meter - Page 1 of 2



| V | iew Online at https://aerobasegroup.com/nsn/6625-00-953-4644 |
|----|--|
| D | ielectric Withstanding Voltage In Volts: |
| 2 | 500.0 |
| 0 | verall Length: |
| 2. | 330 inches |
| M | ounting Hole Diameter: |
| 0. | 128 inches |
| S | cale Division Quantity: |
| 40 | O single indicator single range |
| 0 | verall Diameter: |
| 2. | 690 inches |
| M | ounting Bolt Circle Diameter: |
| 2. | 440 inches |
| In | stallation Design: |
| Ρ | anel |
| M | ounting Arrangement Style: |
| Т | hree hole/stud bolt circle |
| F | requency Response Range: |
| +3 | 360.000 to 440.000 hertz |
| D | ial Scale Marking Color: |
| В | lack single indicator single range |
| Α | ccuracy In Percent: |
| -2 | 2.0 to 2.0 at full scale single indicator single range |
| M | eter Depth Behind Mounting Flange: |
| 2. | 090 inches |
| M | eter Body Diameter Behind Mounting Flange: |
| 2. | 180 inches |
| M | ovement Type: |
| M | oving coil, permanent magnet |
| В | ackground Color: |
| V | hite single indicator single range |
| M | ounting Facility Type And Quantity: |

3 unthreaded hole

Measurement Range:

+380.0 to 420.0 hertz single indicator single range

Features Provided:

Zero adjuster

Movement Suspension Method:

Jewel pivot base

Circuit Attachment Method And Quantity:

2 threaded stud

Style Designator:

C1 round flush mtg

NSN 6625-00-953-4644

Electrical Frequency Meter - Page 2 of 2



| Fsc A | ilaa | catior | n Data: |
|-------|------|--------|---------|
| | | | |

Test set, electronic equipment

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A310a0