## NSN 6625-00-954-6410

Null Meter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6625-00-954-6410

Circuit Current For Which Designed:
Dc
Dielectric Withstanding Voltage In Volts:
3000.0
Overall Length:
1.877 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
5.228 inches
Center To Center Distance Between Mounting Facilities Parallel To Width:
2.977 inches
Overall Height:
4.648 inches
Overall Width:
5.758 inches
Scale Division Quantity:
60 single indicator 2nd range
Mounting Stud Length:
0.497 inches
Environmental Protection:
Airtight and dust resistant and fungus resistant and heat resistant and humidity resistant and shock resistant and vibration resistant and
water resistant
Furnished Items And Quantity:
Nut 6; lockwasher 6; seal 1
Indicator Type:
Dial w/pointer
Installation Design:
Panel
Mounting Arrangement Style:
Four hole/stud rectangular/square
Sensitivity Rating:
3.0 volts
Dial Scale Marking Color:
Black single indicator all ranges
Accuracy In Percent:
-2.0/+2.0 at full scale single indicator all ranges
Meter Depth Behind Mounting Flange:
1.205 inches
Meter Body Diameter Behind Mounting Flange:
2.793 inches
Movement Type:
Moving coil, permanent magnet

White single indicator all ranges

**Background Color:** 

## NSN 6625-00-954-6410

Null Meter - Page 2 of 2



Pointer Color:
Red single indicator all ranges
Scale Marking:
Top scale, 1.0; .8; .6; .4; .2; 0; .2; .4; .6; .8; 1.0; bottom scale, 3; 2; 1; 0; 1; 2; 3
Mounting Facility Type And Quantity:
4 threaded stud
Scale Graduation Type:
Linear single indicator all ranges
Mounting Stud Diameter:
0.136 inches
Features Provided:
Magnetic shield and mirror scale and zero adjuster
Movement Suspension Method:
Jewel pivot base
Circuit Attachment Method And Quantity:
2 threaded stud
Special Features:
Ruggedized
Special Markings:
On back, sealed do not open; on front, -; +
Material:
Plastic
Nuclear Hardness Critical Feature:
Nonhardened
Surface Treatment:
Paint
Special Test Features:
Complies with mil-m-10304
Style Designator:
Rectangular flush mtg
Fsc Application Data:
Test set, elect. Equip.
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A310a0