NSN 6625-00-957-0234

Voltmeter - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/6625-00-957-0234

| Ac Overall Diameter: 3.510 inches Mounting Bolt Circle Diameter: 3.220 inches Installation Design: Panel Mounting Arrangement Style: Three hole/stud bolt circle Frequency Response Range: +390.000/+410.000 hertz Dial Scale Marking Color: Black single indicator single range Accuracy In Percent: -1.0/+1.0 at full scale single indicator all ranges Meter Depth Behind Mounting Flange: 7.250 inches Meter Body Diameter Behind Mounting Flange: 2.860 inches Background Color: White single indicator single range Mounting Facility Type And Quantity: 3 threaded stud Measurement Range: +430.0/+470.0 volts, ac single indicator single range Circuit Attachment Method And Quantity: 2 threaded stud Style Designator: Round flush mtg Shelf Life: N/a | Circuit Current For Which Designed: |
|---|---|
| 3.510 inches Mounting Bolt Circle Diameter: 3.220 inches Installation Design: Panel Mounting Arrangement Style: Three hole/stud bolt circle Frequency Response Range: +390.000/+410.000 hertz Dial Scale Marking Color: Black single indicator single range Accuracy In Percent: -1.0/+1.0 at full scale single indicator all ranges Meter Depth Behind Mounting Flange: 7.250 inches Meter Body Diameter Behind Mounting Flange: 2.860 inches Background Color: White single indicator single range Mounting Facility Type And Quantity: 3 threaded stud Measurement Range: +430.0/+470.0 volts, ac single indicator single range Circuit Attachment Method And Quantity: 2 threaded stud Style Designator: Round flush mtg Shelf Life: N/a | Ac |
| Mounting Bolt Circle Diameter: 3.220 inches Installation Design: Panel Mounting Arrangement Style: Three hole/stud bolt circle Frequency Response Range: +390.000/+410.000 hertz Dial Scale Marking Color: Black single indicator single range Accuracy In Percent: -1.0/+1.0 at full scale single indicator all ranges Meter Depth Behind Mounting Flange: 7.250 inches Meter Body Diameter Behind Mounting Flange: 2.860 inches Background Color: White single indicator single range Mounting Facility Type And Quantity: 3 threaded stud Measurement Range: +430.0/+470.0 volts, ac single indicator single range Circuit Attachment Method And Quantity: 2 threaded stud Style Designator: Round flush mtg Shelf Life: N/a | Overall Diameter: |
| Installation Design: Panel Mounting Arrangement Style: Three hole/stud bolt circle Frequency Response Range: +390.000/+410.000 hertz Dial Scale Marking Color: Black single indicator single range Accuracy In Percent: -1.0/+1.0 at full scale single indicator all ranges Meter Depth Behind Mounting Flange: 7.250 inches Meter Body Diameter Behind Mounting Flange: 2.860 inches Background Color: White single indicator single range Mounting Facility Type And Quantity: 3 threaded stud Measurement Range: +430.0/+470.0 volts, ac single indicator single range Circuit Attachment Method And Quantity: 2 threaded stud Style Designator: Round flush mtg Shelf Life: N/a | 3.510 inches |
| Installation Design: Panel Mounting Arrangement Style: Three hole/stud bolt circle Frequency Response Range: +390.000/+410.000 hertz Dial Scale Marking Color: Black single indicator single range Accuracy In Percent: -1.0/+1.0 at full scale single indicator all ranges Meter Depth Behind Mounting Flange: 7.250 inches Meter Body Diameter Behind Mounting Flange: 2.860 inches Background Color: White single indicator single range Mounting Facility Type And Quantity: 3 threaded stud Measurement Range: +430.0/+470.0 volts, ac single indicator single range Circuit Attachment Method And Quantity: 2 threaded stud Style Designator: Round flush mtg Shelf Life: N/a | Mounting Bolt Circle Diameter: |
| Mounting Arrangement Style: Three hole/stud bolt circle Frequency Response Range: +390.000/+410.000 hertz Dial Scale Marking Color: Black single indicator single range Accuracy In Percent: -1.0/+1.0 at full scale single indicator all ranges Meter Depth Behind Mounting Flange: 7.250 inches Meter Body Diameter Behind Mounting Flange: 2.860 inches Background Color: White single indicator single range Mounting Facility Type And Quantity: 3 threaded stud Measurement Range: +430.0/+470.0 volts, ac single indicator single range Circuit Attachment Method And Quantity: 2 threaded stud Style Designator: Round flush mtg Shelf Life: N/a | 3.220 inches |
| Mounting Arrangement Style: Three hole/stud bolt circle Frequency Response Range: +390.000/+410.000 hertz Dial Scale Marking Color: Black single indicator single range Accuracy In Percent: -1.0/+1.0 at full scale single indicator all ranges Meter Depth Behind Mounting Flange: 7.250 inches Meter Body Diameter Behind Mounting Flange: 2.860 inches Background Color: White single indicator single range Mounting Facility Type And Quantity: 3 threaded stud Measurement Range: +430.0/+470.0 volts, ac single indicator single range Circuit Attachment Method And Quantity: 2 threaded stud Style Designator: Round flush mtg Shelf Life: N/a | Installation Design: |
| Three hole/stud bolt circle Frequency Response Range: +390.000/+410.000 hertz Dial Scale Marking Color: Black single indicator single range Accuracy In Percent: -1.0/+1.0 at full scale single indicator all ranges Meter Depth Behind Mounting Flange: 7.250 inches Meter Body Diameter Behind Mounting Flange: 2.860 inches Background Color: White single indicator single range Mounting Facility Type And Quantity: 3 threaded stud Measurement Range: +430.0/+470.0 volts, ac single indicator single range Circuit Attachment Method And Quantity: 2 threaded stud Style Designator: Round flush mtg Shelf Life: N/a | Panel |
| Frequency Response Range: +390.000/+410.000 hertz Dial Scale Marking Color: Black single indicator single range Accuracy In Percent: -1.0/+1.0 at full scale single indicator all ranges Meter Depth Behind Mounting Flange: 7.250 inches Meter Body Diameter Behind Mounting Flange: 2.860 inches Background Color: White single indicator single range Mounting Facility Type And Quantity: 3 threaded stud Measurement Range: +430.0/+470.0 volts, ac single indicator single range Circuit Attachment Method And Quantity: 2 threaded stud Style Designator: Round flush mtg Shelf Life: N/a | Mounting Arrangement Style: |
| +390.000/+410.000 hertz Dial Scale Marking Color: Black single indicator single range Accuracy In Percent: -1.0/+1.0 at full scale single indicator all ranges Meter Depth Behind Mounting Flange: 7.250 inches Meter Body Diameter Behind Mounting Flange: 2.860 inches Background Color: White single indicator single range Mounting Facility Type And Quantity: 3 threaded stud Measurement Range: +430.0/+470.0 volts, ac single indicator single range Circuit Attachment Method And Quantity: 2 threaded stud Style Designator: Round flush mtg Shelf Life: N/a | Three hole/stud bolt circle |
| Dial Scale Marking Color: Black single indicator single range Accuracy In Percent: -1.0/+1.0 at full scale single indicator all ranges Meter Depth Behind Mounting Flange: 7.250 inches Meter Body Diameter Behind Mounting Flange: 2.860 inches Background Color: White single indicator single range Mounting Facility Type And Quantity: 3 threaded stud Measurement Range: +430.0/+470.0 volts, ac single indicator single range Circuit Attachment Method And Quantity: 2 threaded stud Style Designator: Round flush mtg Shelf Life: N/a | Frequency Response Range: |
| Accuracy In Percent: -1.0/+1.0 at full scale single indicator all ranges Meter Depth Behind Mounting Flange: 7.250 inches Meter Body Diameter Behind Mounting Flange: 2.860 inches Background Color: White single indicator single range Mounting Facility Type And Quantity: 3 threaded stud Measurement Range: +430.0/+470.0 volts, ac single indicator single range Circuit Attachment Method And Quantity: 2 threaded stud Style Designator: Round flush mtg Shelf Life: N/a | +390.000/+410.000 hertz |
| Accuracy In Percent: -1.0/+1.0 at full scale single indicator all ranges Meter Depth Behind Mounting Flange: 7.250 inches Meter Body Diameter Behind Mounting Flange: 2.860 inches Background Color: White single indicator single range Mounting Facility Type And Quantity: 3 threaded stud Measurement Range: +430.0/+470.0 volts, ac single indicator single range Circuit Attachment Method And Quantity: 2 threaded stud Style Designator: Round flush mtg Shelf Life: N/a | Dial Scale Marking Color: |
| -1.0/+1.0 at full scale single indicator all ranges Meter Depth Behind Mounting Flange: 7.250 inches Meter Body Diameter Behind Mounting Flange: 2.860 inches Background Color: White single indicator single range Mounting Facility Type And Quantity: 3 threaded stud Measurement Range: +430.0/+470.0 volts, ac single indicator single range Circuit Attachment Method And Quantity: 2 threaded stud Style Designator: Round flush mtg Shelf Life: N/a | Black single indicator single range |
| Meter Depth Behind Mounting Flange: 7.250 inches Meter Body Diameter Behind Mounting Flange: 2.860 inches Background Color: White single indicator single range Mounting Facility Type And Quantity: 3 threaded stud Measurement Range: +430.0/+470.0 volts, ac single indicator single range Circuit Attachment Method And Quantity: 2 threaded stud Style Designator: Round flush mtg Shelf Life: N/a | Accuracy In Percent: |
| 7.250 inches Meter Body Diameter Behind Mounting Flange: 2.860 inches Background Color: White single indicator single range Mounting Facility Type And Quantity: 3 threaded stud Measurement Range: +430.0/+470.0 volts, ac single indicator single range Circuit Attachment Method And Quantity: 2 threaded stud Style Designator: Round flush mtg Shelf Life: N/a | -1.0/+1.0 at full scale single indicator all ranges |
| Meter Body Diameter Behind Mounting Flange: 2.860 inches Background Color: White single indicator single range Mounting Facility Type And Quantity: 3 threaded stud Measurement Range: +430.0/+470.0 volts, ac single indicator single range Circuit Attachment Method And Quantity: 2 threaded stud Style Designator: Round flush mtg Shelf Life: N/a | Meter Depth Behind Mounting Flange: |
| 2.860 inches Background Color: White single indicator single range Mounting Facility Type And Quantity: 3 threaded stud Measurement Range: +430.0/+470.0 volts, ac single indicator single range Circuit Attachment Method And Quantity: 2 threaded stud Style Designator: Round flush mtg Shelf Life: N/a | 7.250 inches |
| Background Color: White single indicator single range Mounting Facility Type And Quantity: 3 threaded stud Measurement Range: +430.0/+470.0 volts, ac single indicator single range Circuit Attachment Method And Quantity: 2 threaded stud Style Designator: Round flush mtg Shelf Life: N/a | Meter Body Diameter Behind Mounting Flange: |
| White single indicator single range Mounting Facility Type And Quantity: 3 threaded stud Measurement Range: +430.0/+470.0 volts, ac single indicator single range Circuit Attachment Method And Quantity: 2 threaded stud Style Designator: Round flush mtg Shelf Life: N/a | 2.860 inches |
| Mounting Facility Type And Quantity: 3 threaded stud Measurement Range: +430.0/+470.0 volts, ac single indicator single range Circuit Attachment Method And Quantity: 2 threaded stud Style Designator: Round flush mtg Shelf Life: N/a | Background Color: |
| 3 threaded stud Measurement Range: +430.0/+470.0 volts, ac single indicator single range Circuit Attachment Method And Quantity: 2 threaded stud Style Designator: Round flush mtg Shelf Life: N/a | White single indicator single range |
| Measurement Range: +430.0/+470.0 volts, ac single indicator single range Circuit Attachment Method And Quantity: 2 threaded stud Style Designator: Round flush mtg Shelf Life: N/a | Mounting Facility Type And Quantity: |
| +430.0/+470.0 volts, ac single indicator single range Circuit Attachment Method And Quantity: 2 threaded stud Style Designator: Round flush mtg Shelf Life: N/a | 3 threaded stud |
| Circuit Attachment Method And Quantity: 2 threaded stud Style Designator: Round flush mtg Shelf Life: N/a | Measurement Range: |
| 2 threaded stud Style Designator: Round flush mtg Shelf Life: N/a | +430.0/+470.0 volts, ac single indicator single range |
| Style Designator: Round flush mtg Shelf Life: N/a | Circuit Attachment Method And Quantity: |
| Round flush mtg Shelf Life: N/a | 2 threaded stud |
| Shelf Life: N/a | Style Designator: |
| N/a | Round flush mtg |
| | Shelf Life: |
| Unit Of Massura: | N/a |
| Offit Of Micasure. | Unit Of Measure: |
| | |
| Demilitarization: | Demilitarization: |
| Yes - demil/mli | Yes - demil/mli |
| Fiig: | Fiig: |
| A310a0 | A310a0 |