

View Online at <https://aerobasegroup.com/nsn/6625-00-958-4184>

Circuit Current For Which Designed:

Ac

Overall Length:

4.900 inches

Mounting Hole Diameter:

0.112 inches

Scale Division Quantity:

40 single indicator all ranges

Overall Diameter:

2.695 inches

Environmental Protection:

Cold resistant and heat resistant and shock resistant

Mounting Bolt Circle Diameter:

Between 2.430 inches and 2.450 inches

Furnished Items And Quantity:

Nut 6; washer 6

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Three hole/stud bolt circle

Frequency Response Range:

+0.360/+1.600 kilohertz

Dial Scale Marking Color:

White single indicator all ranges

Accuracy In Percent:

-1.0/+1.0 at full scale single indicator 2nd range

Unable To Decode:

Unable to decode or unable to decode

Meter Depth Behind Mounting Flange:

4.125 inches

Meter Body Diameter Behind Mounting Flange:

2.210 inches

Movement Type:

Moving iron vane

Background Color:

Black single indicator all ranges

Pointer Color:

White single indicator all ranges

Power Source:

External

Mounting Facility Type And Quantity:

3 screw and 3 unthreaded hole

Scale Graduation Type:

Linear single indicator all ranges

Measurement Range:

+25.0/+65.0 volts, ac single indicator 1st range

Scale Selection Method:

Terminal

Features Provided:

Rectifier circuit and zero adjuster

Movement Suspension Method:

Taut band

Circuit Attachment Method And Quantity:

3 threaded stud

Special Features:

Ruggedized

Special Markings:

1, 2 and 3 next to term.

Material:

Stainless steel

Nuclear Hardness Critical Feature:

Nonhardened

Surface Treatment:

Enamel semigloss

Style Designator:

Round flush mtg

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A310a0