## NSN 6625-00-961-1601

Ammeter - Page 1 of 2

Dc

Overall Length:

4 threaded stud

**Circuit Current For Which Designed:** 



View Online at https://aerobasegroup.com/nsn/6625-00-961-1601

2.21875 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
3.562 inches
Center To Center Distance Between Mounting Facilities Parallel To Width:
4.000 inches
Overall Height:
4.219 inches
Overall Width:
4.328 inches
Scale Division Quantity:
51 single indicator single range
Mounting Stud Length:
0.375 inches
Furnished Items And Quantity:
Terminal nuts washers 4
Indicator Type:
Dial w/pointer
Installation Design:
Panel
Mounting Arrangement Style:
Four hole/stud rectangular/square
Sensitivity Rating:
100.0 millivolts
Dial Scale Marking Color:
Black single indicator single range
Accuracy In Percent:
-2.0/+2.0 at full scale single indicator single range
Meter Depth Behind Mounting Flange:
0.843 inches
Meter Body Diameter Behind Mounting Flange:
2.750 inches
Movement Type:
Moving coil, permanent magnet
Background Color:
White single indicator single range
Pointer Color:
Black single indicator single range
Mounting Facility Type And Quantity:

## NSN 6625-00-961-1601

Ammeter - Page 2 of 2



Scale Graduation Type:
Linear single indicator single range
Measurement Range:
+0.0/+100.0 milliamperes, dc single indicator single range
Mounting Stud Diameter:
0.138 inches
Features Provided:
Zero adjuster
Circuit Attachment Method And Quantity:
2 threaded stud
Special Markings:
Caption i forward milliamperes center of dial below div scale
Material:
Plastic
Nuclear Hardness Critical Feature:
Nonhardened
Style Designator:
Rectangular flush mtg
Fsc Application Data:
Test set, elect. Equip.
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A310a0