

View Online at <https://aerobasegroup.com/nsn/6625-00-964-2808>

**Circuit Current For Which Designed:**

Ac

**Dielectric Withstanding Voltage In Volts:**

2500.0

**Overall Length:**

2.500 inches

**Mounting Hole Diameter:**

0.140 inches

**Overall Diameter:**

2.690 inches

**Mounting Bolt Circle Diameter:**

2.440 inches

**Indicator Type:**

Dial w/pointer

**Installation Design:**

Panel

**Mounting Arrangement Style:**

Three hole/stud bolt circle

**Frequency Response Range:**

+25.000/+125.000 hertz

**Dial Scale Marking Color:**

Black single indicator all ranges

**Accuracy In Percent:**

-2.0/+2.0 at full scale single indicator all ranges

**Meter Depth Behind Mounting Flange:**

1.390 inches

**Meter Body Diameter Behind Mounting Flange:**

2.100 inches

**Movement Type:**

Moving coil, permanent magnet

**Background Color:**

White single indicator all ranges

**Pointer Color:**

Black single indicator all ranges

**Mounting Facility Type And Quantity:**

3 unthreaded hole

**Scale Graduation Type:**

Nonlinear single indicator all ranges

**Measurement Range:**

+0.0/+3.0 volts, peak to peak single indicator 2nd range

**Scale Selection Method:**

Switch

**Features Provided:**

Zero adjuster

**Movement Suspension Method:**

Jewel pivot base

**Circuit Attachment Method And Quantity:**

2 solder lug and 2 threaded stud

**Special Features:**

Ruggedized

**Nuclear Hardness Critical Feature:**

Nonhardened

**Style Designator:**

Round flush mtg

**Fsc Application Data:**

Test set, electronic equipment

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A310a0