

View Online at <https://aerobasegroup.com/nsn/6625-00-965-6351>

**Circuit Current For Which Designed:**

Dc

**Dielectric Withstanding Voltage In Volts:**

2000.0

**Overall Length:**

2.560 inches

**Mounting Hole Diameter:**

0.112 inches

**Scale Division Quantity:**

25 single indicator single range

**Overall Diameter:**

2.690 inches

**Mounting Bolt Circle Diameter:**

2.440 inches

**Furnished Items And Quantity:**

Washer 3; nut 3

**Indicator Type:**

Dial w/pointer

**Installation Design:**

Panel

**Mounting Arrangement Style:**

Three hole/stud bolt circle

**Sensitivity Rating:**

50.0 microamperes

**Dial Scale Marking Color:**

Black single indicator single range

**Accuracy In Percent:**

-2.0/+2.0 at full scale single indicator single range

**Meter Depth Behind Mounting Flange:**

1.380 inches

**Meter Body Diameter Behind Mounting Flange:**

2.050 inches

**Movement Type:**

Moving coil, permanent magnet

**Background Color:**

White single indicator single range

**Pointer Color:**

Black single indicator single range

**Scale Marking:**

0; 20; 40; 60; 80; 100

**Mounting Facility Type And Quantity:**

3 screw and 3 unthreaded hole

**Scale Graduation Type:**

Linear single indicator single range

**Features Provided:**

Self-illumination facility and zero adjuster

**Movement Suspension Method:**

Jewel pivot base

**Circuit Attachment Method And Quantity:**

2 solder lug and 2 threaded stud

**Special Features:**

Ruggedized

**Material:**

Steel

**Nuclear Hardness Critical Feature:**

Nonhardened

**Surface Treatment:**

Chromate and zinc

**Style Designator:**

Round flush mtg

**Fsc Application Data:**

Test set, elect. Equip.

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A310a0