

View Online at <https://aerobasegroup.com/nsn/6625-00-965-7821>

**Circuit Current For Which Designed:**

Dc

**Dielectric Withstanding Voltage In Volts:**

3000.0

**Overall Length:**

2.650 inches

**Mounting Hole Diameter:**

0.125 inches

**Scale Division Quantity:**

50 single indicator single range

**Overall Diameter:**

2.695 inches

**Environmental Protection:**

Airtight and dust resistant and fungus resistant and heat resistant and humidity resistant and shock resistant and vibration resistant and water resistant

**Mounting Bolt Circle Diameter:**

2.440 inches

**Furnished Items And Quantity:**

Nut 7; lockwasher 5; seal 1

**Indicator Type:**

Dial w/pointer

**Installation Design:**

Panel

**Mounting Arrangement Style:**

Three hole/stud bolt circle

**Dial Scale Marking Color:**

White single indicator single range

**Accuracy In Percent:**

-2.0/+2.0 at full scale single indicator all ranges

**Meter Depth Behind Mounting Flange:**

1.600 inches

**Meter Body Diameter Behind Mounting Flange:**

2.210 inches

**Movement Type:**

Moving iron vane

**Background Color:**

Black single indicator single range

**Pointer Color:**

White single indicator single range

**Power Source:**

External

**Mounting Facility Type And Quantity:**

3 unthreaded hole

**Scale Graduation Type:**

Linear single indicator single range

**Measurement Range:**

+0.0/+50.0 volts, dc single indicator single range

**Scale Selection Method:**

Terminal

**Features Provided:**

Magnetic shield

**Circuit Attachment Method And Quantity:**

2 threaded stud and 2 solder lug

**Special Features:**

Ruggedized

**Material:**

Plastic

**Nuclear Hardness Critical Feature:**

Nonhardened

**Special Test Features:**

Complies with mil-m-10304

**Style Designator:**

Round flush mtg

**Test Data Document:**

81349-mil-m-10304 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Specification Data:**

81349-mil-m-10304/4 government specification

**Fsc Application Data:**

Test set, elect. Equip.

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A310a0