NSN 6625-00-968-7043

Ammeter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6625-00-968-7043

Circuit Current For Which Designed:

Dc

Overall Length:

2.496 inches

Overall Height:

0.515 inches

Overall Width:

1.600 inches

Mounting Hole Diameter:

0.093 inches

Scale Division Quantity:

50 single indicator single range

Environmental Protection:

Dustproof

Distance Between Mounting Facility Centers:

1.258 inches

Barrel Width:

1.600 inches

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Two hole/stud

Dial Scale Marking Color:

Black single indicator single range

Accuracy In Percent:

-3.0/+3.0 at full scale single indicator single range

Meter Depth Behind Mounting Flange:

2.260 inches

Meter Body Width Behind Mounting Flange:

1.600 inches

Movement Type:

Moving coil, permanent magnet

Background Color:

White single indicator single range

Pointer Color:

Black single indicator single range

Power Source:

External

Mounting Facility Type And Quantity:

2 unthreaded hole

NSN 6625-00-968-7043

Ammeter - Page 2 of 2



| Scale Graduation Ty | |
|---------------------------|-------------------------------------|
| Linear single indicato | |
| Measurement Range | |
| | s, dc single indicator single range |
| Scale Selection Met | lod: |
| Switch | |
| | ehind Mounting Flange: |
| 0.965 inches | |
| Meter Barrel Depth: | |
| 1.622 inches | |
| Features Provided: | |
| Zero adjuster | an Mathadi |
| Movement Suspens | on method: |
| Jewel pivot base | Jothad And Quantity |
| | lethod And Quantity: |
| 2 solder lug Material: | |
| Plastic | |
| Nuclear Hardness C | itical Feature |
| Nonhardened | |
| Style Designator: | |
| Rectangular flush mto | barrel right |
| Fsc Application Dat | |
| Test set electronic | |
| Shelf Life: | |
| N/a | |
| Unit Of Measure: | |
| | |
| Demilitarization: | |
| No | |
| Fiig: | |
| A310a0 | |