

View Online at <https://aerobasegroup.com/nsn/6625-00-968-7573>

Circuit Current For Which Designed:

Dc

Dielectric Withstanding Voltage In Volts:

1500.0

Overall Length:

1.500 inches

Mounting Hole Diameter:

0.090 inches

Scale Division Quantity:

10 single indicator single range

Overall Diameter:

1.360 inches

Mounting Bolt Circle Diameter:

1.187 inches

Furnished Items And Quantity:

Nut 3; washer 3

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Three hole/stud bolt circle

Dial Scale Marking Color:

Black single indicator single range

Accuracy In Percent:

-3.0/+3.0 at full scale single indicator single range

Meter Depth Behind Mounting Flange:

0.860 inches

Meter Body Diameter Behind Mounting Flange:

0.987 inches

Movement Type:

Moving coil, permanent magnet

Background Color:

White single indicator single range

Pointer Color:

Black single indicator single range

Power Source:

External

Mounting Facility Type And Quantity:

4 unthreaded hole

Scale Graduation Type:

Linear single indicator single range

Measurement Range:

+0.0/+100.0 microamps single indicator single range

Features Provided:

Zero adjuster

Movement Suspension Method:

Jewel pivot base

Circuit Attachment Method And Quantity:

2 solder lug

Material:

Aluminum

Nuclear Hardness Critical Feature:

Nonhardened

Special Test Features:

Mark per mil-std-130

Style Designator:

Round flush mtg

Supplementary Features:

Lance type pointer

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A310a0