

View Online at <https://aerobasegroup.com/nsn/6625-00-969-4105>

Circuit Current For Which Designed:

Ac

Overall Length:

11.000 inches

Overall Height:

6.500 inches

Overall Width:

5.125 inches

Scale Division Quantity:

50 single indicator 2nd range

Frequency Rating:

Between 50.000 hertz and 1.000 kilohertz

Indicator Type:

Dial w/pointer

Installation Design:

Bench

Sensitivity Rating:

1.0 milliamperes

Dial Scale Marking Color:

Black single indicator all ranges

Accuracy In Percent:

-3.0/+3.0 at full scale single indicator 3rd range

Pointer Color:

Black single indicator all ranges

Scale Graduation Type:

Nonlinear single indicator 4th range

Measurement Range:

-1500.0/+1500.0 volts, dc single indicator 2nd range

Features Provided:

Autoranging

Accuracy Rating:

Pct of range plus pct of reading single indicator all ranges

Circuit Attachment Method And Quantity:

3 clip and 1 probe, direct contact

Operating Voltage Rating In Volts:

Between 115.0 ac and 230.0 ac

Phase:

Single

Special Features:

Ranges for vac, 7 ranges-.5, 1.5, 5 sequence; vdc ranges 11 ranges-15, 50 sequence; dc amps, 11 ranges 1.5, 5 sequence; ohms-7 ranges; includes db display reference

Reference Data And Literature:

To 33a1-12-704-11

Surface Treatment:

Enamel

Style Designator:

D1 rectangular or square

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A310a0