

View Online at <https://aerobasegroup.com/nsn/6625-00-972-2467>

Circuit Current For Which Designed:

Ac

Overall Length:

1.450 inches

Mounting Hole Diameter:

0.150 inches

Overall Diameter:

3.510 inches

Environmental Protection:

Dustproof

Mounting Bolt Circle Diameter:

3.160 inches

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Three hole/stud bolt circle

Frequency Response Range:

+50.000/+60.000 hertz

Dial Scale Marking Color:

Black single indicator all ranges

Accuracy In Percent:

-1.5/+1.5 at full scale single indicator all ranges

Meter Depth Behind Mounting Flange:

1.250 inches

Meter Body Diameter Behind Mounting Flange:

2.670 inches

Movement Type:

Moving coil, permanent magnet

Background Color:

White single indicator all ranges

Pointer Color:

Black single indicator all ranges

Power Source:

External

Mounting Facility Type And Quantity:

3 unthreaded hole

Scale Graduation Type:

Nonlinear single indicator all ranges

Measurement Range:

+0.0/+150.0 amperes, ac single indicator 2nd range

Scale Selection Method:

Terminal

Features Provided:

Zero adjuster

Movement Suspension Method:

Jewel pivot base

Circuit Attachment Method And Quantity:

2 threaded stud

Special Markings:

Blue line at 100 on 50 hz scale, red line at 100 on 60 hz scale

Material:

Steel

Nuclear Hardness Critical Feature:

Nonhardened

Surface Treatment:

Enamel semigloss

Style Designator:

Round flush mtg

Fsc Application Data:

Test set electronic

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A310a0