

View Online at <https://aerobasegroup.com/nsn/6625-00-978-2851>

Circuit Current For Which Designed:

Ac

Dielectric Withstanding Voltage In Volts:

2000.0

Overall Length:

2.000 inches

Mounting Hole Diameter:

Between 0.148 inches and 0.152 inches

Overall Diameter:

3.510 inches

Mounting Bolt Circle Diameter:

3.160 inches

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Three hole/stud bolt circle

Sensitivity Rating:

200.0 microamperes

Dial Scale Marking Color:

Yellow single indicator 3rd range

Accuracy In Percent:

-1.0/+1.0 at full scale single indicator all ranges

Meter Depth Behind Mounting Flange:

1.660 inches

Meter Body Diameter Behind Mounting Flange:

2.800 inches

Movement Type:

Moving iron vane

Background Color:

Gray single indicator all ranges

Pointer Color:

Black single indicator all ranges

Scale Marking:

Black band from 0 to 25 microamperes; red band from 67.3 to 119.23 microamperes; yellow band from 86.5 to 119.23 microamperes

Mounting Facility Type And Quantity:

3 unthreaded hole

Scale Graduation Type:

Nonlinear single indicator all ranges

Features Provided:

Knife edge pointer and zero adjuster

Movement Suspension Method:

Taut band

Circuit Attachment Method And Quantity:

2 screw and 2 solder lug

Nuclear Hardness Critical Feature:

Nonhardened

Surface Treatment:

Enamel semigloss

Style Designator:

Round flush mtg

Supplementary Features:

Internal resistance: 2100 ohms ; damping factor: 7.5

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A310a0