

View Online at <https://aerobasegroup.com/nsn/6625-00-978-2851>

**Circuit Current For Which Designed:**

Ac

**Dielectric Withstanding Voltage In Volts:**

2000.0

**Overall Length:**

2.000 inches

**Mounting Hole Diameter:**

Between 0.148 inches and 0.152 inches

**Overall Diameter:**

3.510 inches

**Mounting Bolt Circle Diameter:**

3.160 inches

**Indicator Type:**

Dial w/pointer

**Installation Design:**

Panel

**Mounting Arrangement Style:**

Three hole/stud bolt circle

**Sensitivity Rating:**

200.0 microamperes

**Dial Scale Marking Color:**

Yellow single indicator 3rd range

**Accuracy In Percent:**

-1.0/+1.0 at full scale single indicator all ranges

**Meter Depth Behind Mounting Flange:**

1.660 inches

**Meter Body Diameter Behind Mounting Flange:**

2.800 inches

**Movement Type:**

Moving iron vane

**Background Color:**

Gray single indicator all ranges

**Pointer Color:**

Black single indicator all ranges

**Scale Marking:**

Black band from 0 to 25 microamperes; red band from 67.3 to 119.23 microamperes; yellow band from 86.5 to 119.23 microamperes

**Mounting Facility Type And Quantity:**

3 unthreaded hole

**Scale Graduation Type:**

Nonlinear single indicator all ranges

**Features Provided:**

Knife edge pointer and zero adjuster

**Movement Suspension Method:**

Taut band

**Circuit Attachment Method And Quantity:**

2 screw and 2 solder lug

**Nuclear Hardness Critical Feature:**

Nonhardened

**Surface Treatment:**

Enamel semigloss

**Style Designator:**

Round flush mtg

**Supplementary Features:**

Internal resistance: 2100 ohms ; damping factor: 7.5

**Fsc Application Data:**

Test set, elect. Equip.

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A310a0