

View Online at <https://aerobasegroup.com/nsn/6625-00-979-9123>

Circuit Current For Which Designed:

Dc

Dielectric Withstanding Voltage In Volts:

1500.0

Mounting Hole Diameter:

0.125 inches

Overall Diameter:

2.695 inches

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Three hole/stud bolt circle

Dial Scale Marking Color:

Black single indicator all ranges

Accuracy In Percent:

-1.0/+1.0 at full scale single indicator all ranges

Meter Body Diameter Behind Mounting Flange:

2.210 inches

Movement Type:

Moving coil, permanent magnet

Background Color:

White single indicator all ranges

Pointer Color:

Black single indicator all ranges

Scale Marking:

3 bands: 1 red at lower end of scale; 1 green at center scale with vertical rectangle dotted in center; 1 red at upper end of scale

Mounting Facility Type And Quantity:

3 unthreaded hole

Scale Graduation Type:

Nonlinear single indicator all ranges

Features Provided:

Magnetic shield and zero adjuster

Movement Suspension Method:

Jewel pivot base

Circuit Attachment Method And Quantity:

4 solderless lug

Special Features:

Terminal identification data: 1 plus 28 volts, 1 plus 15 volts, 1 minus and 1 ground

Special Markings:

15 v reg beneath vertical rectangle on scale; voltage beneath scale

Nuclear Hardness Critical Feature:

Nonhardened

Style Designator:

Round flush mtg

Supplementary Features:

Insulation resistance: 20 megohms from terminals to meter case

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A310a0