

View Online at <https://aerobasegroup.com/nsn/6625-00-979-9123>

**Circuit Current For Which Designed:**

Dc

**Dielectric Withstanding Voltage In Volts:**

1500.0

**Mounting Hole Diameter:**

0.125 inches

**Overall Diameter:**

2.695 inches

**Indicator Type:**

Dial w/pointer

**Installation Design:**

Panel

**Mounting Arrangement Style:**

Three hole/stud bolt circle

**Dial Scale Marking Color:**

Black single indicator all ranges

**Accuracy In Percent:**

-1.0/+1.0 at full scale single indicator all ranges

**Meter Body Diameter Behind Mounting Flange:**

2.210 inches

**Movement Type:**

Moving coil, permanent magnet

**Background Color:**

White single indicator all ranges

**Pointer Color:**

Black single indicator all ranges

**Scale Marking:**

3 bands: 1 red at lower end of scale; 1 green at center scale with vertical rectangle dotted in center; 1 red at upper end of scale

**Mounting Facility Type And Quantity:**

3 unthreaded hole

**Scale Graduation Type:**

Nonlinear single indicator all ranges

**Features Provided:**

Magnetic shield and zero adjuster

**Movement Suspension Method:**

Jewel pivot base

**Circuit Attachment Method And Quantity:**

4 solderless lug

**Special Features:**

Terminal identification data: 1 plus 28 volts, 1 plus 15 volts, 1 minus and 1 ground

**Special Markings:**

15 v reg beneath vertical rectangle on scale; voltage beneath scale

**Nuclear Hardness Critical Feature:**

Nonhardened

**Style Designator:**

Round flush mtg

**Supplementary Features:**

Insulation resistance: 20 megohms from terminals to meter case

**Fsc Application Data:**

Test set, elect. Equip.

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A310a0