NSN 6625-00-979-9144

Voltmeter - Page 1 of 2

Dc

Circuit Current For Which Designed:



View Online at https://aerobasegroup.com/nsn/6625-00-979-9144

| Overall Length: |
|---|
| 2.820 inches |
| Mounting Hole Diameter: |
| 0.150 inches |
| Scale Division Quantity: |
| 50 single indicator all ranges |
| Overall Diameter: |
| 3.510 inches |
| Mounting Bolt Circle Diameter: |
| 3.160 inches |
| Indicator Type: |
| Dial w/pointer |
| Installation Design: |
| Panel |
| Mounting Arrangement Style: |
| Three hole/stud bolt circle |
| Dial Scale Marking Color: |
| Black single indicator all ranges |
| Accuracy In Percent: |
| -2.0/+2.0 at full scale single indicator all ranges |
| Meter Depth Behind Mounting Flange: |
| 2.800 inches |
| Meter Body Diameter Behind Mounting Flange: |
| 2.420 inches |
| Movement Type: |
| Moving iron vane |
| Background Color: |
| White single indicator all ranges |
| Pointer Color: |
| Black single indicator all ranges |
| Power Source: |
| External |
| Mounting Facility Type And Quantity: |
| 3 unthreaded hole |
| Scale Graduation Type: |
| Linear single indicator all ranges |
| Measurement Range: |
| +0.0/+500.0 volts, dc single indicator 3rd range |
| Scale Selection Method: |
| |

NSN 6625-00-979-9144 Voltmeter - Page 2 of 2



| Features Provided: | |
|---|--|
| Zero adjuster | |
| Movement Suspension Method: | |
| Taut band | |
| Circuit Attachment Method And Quantity: | |
| 2 binding post | |
| Special Features: | |
| Ruggedized | |
| Special Markings: | |
| Lh terminal marked positive | |
| Nuclear Hardness Critical Feature: | |
| Nonhardened | |
| Style Designator: | |
| Round flush mtg | |
| Fsc Application Data: | |
| Test set, elect. Equip. | |
| Shelf Life: | |
| N/a | |
| Unit Of Measure: | |
| | |
| Demilitarization: | |
| No | |
| Fiig: | |
| A310a0 | |
| | |