

View Online at <https://aerobasegroup.com/nsn/6625-00-979-9157>

Circuit Current For Which Designed:

Dc

Dielectric Withstanding Voltage In Volts:

3000.0

Overall Length:

2.530 inches

Scale Division Quantity:

6 single indicator single range

Overall Diameter:

2.680 inches

Mounting Bolt Circle Diameter:

2.440 inches

Furnished Items And Quantity:

Lockwasher 3, nuts 3, screws 3

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Three hole/stud bolt circle

Sensitivity Rating:

1.0 milliamperes

Dial Scale Marking Color:

Black single indicator single range

Accuracy In Percent:

-2.0/+2.0 at full scale single indicator single range

Unable To Decode:

Unable to decode or unable to decode

Meter Depth Behind Mounting Flange:

1.100 inches

Meter Body Diameter Behind Mounting Flange:

2.150 inches

Movement Type:

Moving coil, permanent magnet

Background Color:

White single indicator single range

Pointer Color:

Black single indicator single range

Scale Marking:

0; .25; .5; set; p; 1.4; p; relative rf power

Scale Graduation Type:

Nonlinear single indicator single range

Movement Suspension Method:

Jewel pivot base

Circuit Attachment Method And Quantity:

2 solder stud

Special Markings:

Sred segment covers from 0 to 0.75 characteristic numerals, yellow segment covers from 0.75 to 1.2 characteristic numerals, green segment covers from 1.2 to 3.0 characteristic numerals; calibration scale consisting of 9 calibration markings covering a range of 1.2 to 0.8 is located above the red and yellow segments with the calibration numerals 1.0 in line w the 0.75 numeral on the main scale marking; captions mw, rf average power is located in center and below characteristic scale

Material:

Steel

Nuclear Hardness Critical Feature:

Nonhardened

Surface Treatment:

Paint

Style Designator:

Round flush mtg

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A310a0