NSN 6625-00-983-6712

Signal Generator - Page 1 of 2

Mounting Type:



View Online at https://aerobasegroup.com/nsn/6625-00-983-6712

| Bench |
|--------------------------------------|
| Overall Length: |
| 18.375 inches |
| Overall Height: |
| 10.375 inches |
| Overall Width: |
| 16.750 inches |
| Current Type: |
| Ac |
| Frequency Rating: |
| Between 50.0 hertz and 60.0 hertz |
| Case Material: |
| Steel |
| Case Surface Treatment: |
| Enameled |
| Frequency Range Rating: |
| +54.000/+216.000 megahertz |
| Accessory Component Quantity: |
| 1 |
| Accessory Controlling Agency: |
| Booton radio corp |
| Accessory Identifying Number: |
| 502-b type no. |
| Internal Battery Accommodation: |
| Not included |
| Output Impedance Rating: |
| 50.0 ohms |
| Voltage Rating: |
| 250.0 volts |
| Frequency Band Quantity: |
| 2 |
| Modulation Type: |
| Am and pulse |
| Accessory Component Name: |
| Patching cable |
| Calibration Accuracy Rating: |
| Porm 0.5 pct |
| Crystal Controlled Feature: |
| Not provided |
| Calibrated Signal Output Range: |
| 0.1 uv to 2 v |

NSN 6625-00-983-6712

Signal Generator - Page 2 of 2



| Signal Output Constancy: |
|---|
| Porm 1 db maximum variations from 5 cps to 200 kc |
| Modulator Location: |
| External |
| Modulated Frequency Rating: |
| 400.0 hertz |
| Modulation Degree: |
| 100.0 percent |
| Phase: |
| Single |
| Functional Classification: |
| Bb-1.1 |
| Entry Date: |
| 91-02-08 |
| Fsc Application Data: |
| Generator, signal, except specially designed |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| Yes - demil/mli |
| Fiig: |
| T320-j |