

View Online at <https://aerobasegroup.com/nsn/6625-00-983-6727>

Circuit Current For Which Designed:

Dc

Reliability Indicator:

Not established

Overall Length:

2.850 inches

Mounting Hole Diameter:

0.150 inches

Scale Division Quantity:

5 single indicator single range

Overall Diameter:

4.500 inches

Mounting Bolt Circle Diameter:

4.125 inches

End Application:

Aircraft hercules c-130, f-111, galaxy c-5, starlifter c-141, eagle f-15, thunderbolt ii a-10, f-16, aircraft support equipment ov-10a, c-5, t-37, f-106, t-38, b-52, u-2

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Six hole/stud bolt circle

Sensitivity Rating:

50.0 millivolts

Dial Scale Marking Color:

Black single indicator single range

Accuracy In Percent:

-2.0/+2.0 at full scale single indicator single range

Meter Depth Behind Mounting Flange:

1.500 inches

Meter Body Diameter Behind Mounting Flange:

3.750 inches

Movement Type:

Moving coil, permanent magnet

Background Color:

White single indicator single range

Pointer Color:

Black single indicator single range

Mounting Facility Type And Quantity:

6 unthreaded hole

Scale Graduation Type:

Linear single indicator single range

Measurement Range:

-10.0/+10.0 amperes, dc single indicator single range

Features Provided:

Zero adjuster

Criticality Code Justification:

Feat

Movement Suspension Method:

Jewel pivot base

Circuit Attachment Method And Quantity:

2 solder stud

Special Features:

Weapon system essential

Style Designator:

C1 round flush mtg

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A310a0