

View Online at <https://aerobasegroup.com/nsn/6625-00-984-7260>

Circuit Current For Which Designed:

Ac

Overall Length:

4.156 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

5.625 inches

Center To Center Distance Between Mounting Facilities Parallel To Width:

6.000 inches

Overall Height:

6.875 inches

Overall Width:

6.625 inches

Scale Division Quantity:

150 single indicator 3rd range

Frequency Rating:

Between 60.000 hertz and 400.000 hertz

Mounting Stud Length:

0.875 inches

Furnished Items And Quantity:

Mtg hdw 4; term. Hdw 2

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Four hole/stud rectangular/square

Sensitivity Rating:

100.0 milliamperes

Dial Scale Marking Color:

Red single indicator 2nd range

Accuracy In Percent:

-0.25/+0.25 at full scale single indicator all ranges

Meter Depth Behind Mounting Flange:

3.156 inches

Meter Body Width Behind Mounting Flange:

6.125 inches

Movement Type:

Moving coil, permanent magnet

Background Color:

White single indicator all ranges

Pointer Color:

Black single indicator all ranges

Power Source:

External

Mounting Facility Type And Quantity:

4 threaded stud

Scale Graduation Type:

Linear single indicator all ranges

Measurement Range:

+0.0/+30.0 volts, ac single indicator 2nd range

Mounting Stud Diameter:

0.164 inches

Scale Selection Method:

Terminal

Meter Body Height Behind Mounting Flange:

6.375 inches

Features Provided:

Knife edge pointer and mirror scale

Movement Suspension Method:

Jewel pivot base

Circuit Attachment Method And Quantity:

4 threaded stud

Phase:

Single

Nuclear Hardness Critical Feature:

Nonhardened

Surface Treatment:

Enamel

Style Designator:

Rectangular flush mtg

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A310a0