

View Online at <https://aerobasegroup.com/nsn/6625-00-984-7260>

**Circuit Current For Which Designed:**

Ac

**Overall Length:**

4.156 inches

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

5.625 inches

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

6.000 inches

**Overall Height:**

6.875 inches

**Overall Width:**

6.625 inches

**Scale Division Quantity:**

150 single indicator 3rd range

**Frequency Rating:**

Between 60.000 hertz and 400.000 hertz

**Mounting Stud Length:**

0.875 inches

**Furnished Items And Quantity:**

Mtg hdw 4; term. Hdw 2

**Indicator Type:**

Dial w/pointer

**Installation Design:**

Panel

**Mounting Arrangement Style:**

Four hole/stud rectangular/square

**Sensitivity Rating:**

100.0 milliamperes

**Dial Scale Marking Color:**

Red single indicator 2nd range

**Accuracy In Percent:**

-0.25/+0.25 at full scale single indicator all ranges

**Meter Depth Behind Mounting Flange:**

3.156 inches

**Meter Body Width Behind Mounting Flange:**

6.125 inches

**Movement Type:**

Moving coil, permanent magnet

**Background Color:**

White single indicator all ranges

**Pointer Color:**

Black single indicator all ranges

**Power Source:**

External

**Mounting Facility Type And Quantity:**

4 threaded stud

**Scale Graduation Type:**

Linear single indicator all ranges

**Measurement Range:**

+0.0/+30.0 volts, ac single indicator 2nd range

**Mounting Stud Diameter:**

0.164 inches

**Scale Selection Method:**

Terminal

**Meter Body Height Behind Mounting Flange:**

6.375 inches

**Features Provided:**

Knife edge pointer and mirror scale

**Movement Suspension Method:**

Jewel pivot base

**Circuit Attachment Method And Quantity:**

4 threaded stud

**Phase:**

Single

**Nuclear Hardness Critical Feature:**

Nonhardened

**Surface Treatment:**

Enamel

**Style Designator:**

Rectangular flush mtg

**Fsc Application Data:**

Test set, elect. Equip.

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A310a0