

View Online at <https://aerobasegroup.com/nsn/6625-00-985-5019>

Circuit Current For Which Designed:

Ac

Overall Length:

2.000 inches

Mounting Hole Diameter:

Between 0.143 inches and 0.157 inches

Overall Diameter:

3.500 inches

Environmental Protection:

Dust resistant and humidity resistant and water resistant

Mounting Bolt Circle Diameter:

3.160 inches

Furnished Items And Quantity:

Nut 3; washer 3

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Three hole/stud bolt circle

Dial Scale Marking Color:

Black single indicator single range

Accuracy In Percent:

-2.0/+2.0 at full scale single indicator single range

Unable To Decode:

Unable to decode or unable to decode

Meter Depth Behind Mounting Flange:

1.200 inches

Meter Body Diameter Behind Mounting Flange:

2.670 inches

Movement Type:

Moving iron vane

Background Color:

White single indicator single range

Pointer Color:

Black single indicator single range

Scale Marking:

Percentage of full load current; 0, 30, 60, 90, 120, 130

Mounting Facility Type And Quantity:

3 screw and 3 unthreaded hole

Scale Graduation Type:

Nonlinear single indicator single range

Features Provided:

Zero adjuster

Movement Suspension Method:

Taut band

Circuit Attachment Method And Quantity:

2 screw and 2 solder lug

Special Features:

Ruggedized

Special Markings:

Red line at 100 percent; sealed do not open on back

Material:

Steel

Nuclear Hardness Critical Feature:

Nonhardened

Surface Treatment:

Paint

Style Designator:

Round flush mtg

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A310a0