

View Online at <https://aerobasegroup.com/nsn/6625-00-986-4940>

Overall Length:

22.750 inches

Overall Height:

14.000 inches

Overall Width:

19.000 inches

Current Type:

Ac

Accessory Components And Quantity:

Adapter, connector 2, filter light 1, elad, electrical 1, lead, test 2

Voltage Rating:

115.0 volts and 235.0 volts

Beam Quantity:

1

Graduation Interval:

Graduated in v/cm on both axes

Mounting Method:

Rack

Accuracy Range In Percent:

-3.0/+3.0

Screen Size:

5.000 in.

Sweep Circuits:

Included

Generator Driven Feature:

Included

Sweep Circuit Type:

Horizontal

Single Trigger Sweep Duration:

Between 0.1 microseconds and 12.0 seconds

Trigger Sweep Voltage Amplitude Rating:

0.02 volts

Trigger Sweep Polarity Switch:

Included

Expanded Sweep:

Provided

Amplifier Deflection Sensitivity Provision:

Provided

Vertical Deflection Sensitivity Voltage Rating:

0.0045 volts rms per inch and 1.8000 volts rms per inch

Horizontal Deflection Sensitivity Voltage Rating:

0.018 volts cw outside diameter and 1.350 volts peak outside diameter

Input Intensity Modulation Feature:

Not provided

Plate Direct Connection Deflection Sensitivity Provision:

Provided

Direct Connection Vertical Deflection Sensitivity Voltage Rating:

0.882 volts any acceptable outside diameter

Direct Connection Horizontal Deflection Sensitivity Voltage Rating:

2.7 volts rms per inch

Frequency Response Rating:

Provided

Amplifier Input Impedance Rating Provision:

Provided

X-axis Input Impedance Rating:

0.0 kilohms

Y-axis Input Impedance Rating:

1.0 megohms

Amplitude Calibrating Voltage Waveform:

Square wave

Calibrating Peak To Peak Amplitude:

Between 0.2 millivolts and 100.0 volts

Measurement Range Quantity:

2

Measurement Range Steps:

0 to 100 v per cm

Calibrated Screen Scale:

Included

Trace Storage Tube:

Not included

Plug In Unit Function And Quantity:

1 vertical preamplifier

Camera Recording Device Accommodation:

Provided

Phase:

Single

Special Features:

Frequency rating: 50 to 60; x-axis frequency response rating: kc240.0 per sec; y-axis frequency response rating: 0 to 15 mc

Fsc Application Data:

Oscilloscopes, except specially designed

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T320-g