

View Online at <https://aerobasegroup.com/nsn/6625-00-988-1622>

Circuit Current For Which Designed:

Dc

Overall Length:

1.923 inches

Mounting Hole Diameter:

0.145 inches

Scale Division Quantity:

9 single indicator 1st range

Overall Diameter:

3.477 inches

Environmental Protection:

Dust resistant and fungus resistant and heat resistant and shock resistant and vibration resistant

Mounting Bolt Circle Diameter:

3.038 inches

Furnished Items And Quantity:

Nut 3; lockwasher 3; seal 1; shunt wire 1

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Three hole/stud bolt circle

Dial Scale Marking Color:

Black single indicator all ranges

Accuracy In Percent:

-2.0/+2.0 at full scale single indicator all ranges

Meter Depth Behind Mounting Flange:

1.308 inches

Meter Body Diameter Behind Mounting Flange:

2.732 inches

Movement Type:

Moving coil, permanent magnet

Background Color:

White single indicator all ranges

Pointer Color:

Black single indicator all ranges

Power Source:

External

Mounting Facility Type And Quantity:

3 screw and 3 unthreaded hole

Scale Graduation Type:

Nonlinear single indicator 2nd range

Measurement Range:

+4.0/+13.0 decibels single indicator 2nd range

Scale Selection Method:

Terminal

Features Provided:

External shunting and zero adjuster

Movement Suspension Method:

Jewel pivot base

Circuit Attachment Method And Quantity:

2 solder lug

Special Features:

Sealed

Special Markings:

Output volts on top of meter face and set level on bottom of scale and a arrow at 7db

Material:

Plastic

Nuclear Hardness Critical Feature:

Nonhardened

Special Test Features:

Complies with mil-m-10304

Style Designator:

Round flush mtg

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A310a0