NSN 6625-00-988-2558

Ohmmeter - Page 1 of 2

Style Designator:

Portable



View Online at https://aerobasegroup.com/nsn/6625-00-988-2558

| Circuit Current For Which Decigned |
|--|
| Circuit Current For Which Designed: Ac |
| Overall Depth: |
| 6.000 inches |
| Overall Length: |
| 8.875 inches |
| Overall Width: |
| 8.500 inches |
| |
| Frequency Rating: 60.0 hertz |
| |
| Indicator Type: |
| Dial w/pointer |
| Installation Design: |
| Bench Biol Cools Marking Colors |
| Dial Scale Marking Color: |
| Black single indicator single range |
| Accuracy In Percent: |
| -5.0/+5.0 at full scale single indicator 2nd range |
| Pointer Color: |
| Black single indicator single range |
| Scale Graduation Type: |
| Nonlinear single indicator single range |
| Measurement Range: |
| +1.0/+10000000.0 megohms single indicator 1st range |
| Scale Selection Method: |
| Switch |
| Features Provided: |
| Portable |
| Circuit Attachment Method And Quantity: |
| 2 clip |
| Operating Voltage Rating In Volts: |
| 115.0 ac |
| Phase: |
| Single |
| Special Features: |
| Mfg name-vibrotest megohmmeter |
| Functional Description: |
| Measure resistance on printed circuits, transistors, mina circuit components, cables, motors, etc; measure leakakage resistance of |
| capacitors; measure grounded/ungrounded sections of 3-terminal resistors |
| Reference Data And Literature: |
| 33a1-11-44-1 |

NSN 6625-00-988-2558

Ohmmeter - Page 2 of 2



| ς | unn | lem | enta | rv F | eatu | res. |
|---|-----|-------|-------|------|------|--------|
| J | นมม | IGIII | Elila | IVE | eatu | II E5. |

6 megohm ranges at each voltage of 500 vdc, 100 vdc, 50 vdc; removable cover; handle; two 5-ft. Test leads

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A310a0