

View Online at <https://aerobasegroup.com/nsn/6625-00-988-4443>

Circuit Current For Which Designed:

Ac

Overall Length:

2.820 inches

Mounting Hole Diameter:

0.150 inches

Scale Division Quantity:

60 single indicator single range

Overall Diameter:

3.500 inches

Mounting Bolt Circle Diameter:

3.160 inches

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Three hole/stud bolt circle

Sensitivity Rating:

20.0 ohms per volt

Dial Scale Marking Color:

Black single indicator single range

Accuracy In Percent:

-2.0/+2.0 at full scale single indicator single range

Meter Depth Behind Mounting Flange:

1.390 inches

Meter Body Diameter Behind Mounting Flange:

2.760 inches

Movement Type:

Moving iron vane

Background Color:

White single indicator single range

Pointer Color:

Black single indicator single range

Power Source:

External

Mounting Facility Type And Quantity:

3 unthreaded hole

Scale Graduation Type:

Linear single indicator single range

Measurement Range:

+0.0/+600.0 volts, ac single indicator single range

Features Provided:

Magnetic shield

Movement Suspension Method:

Taut band

Circuit Attachment Method And Quantity:

2 solder lug

Special Markings:

Red mark at 120, 208, 240 and 416 v

Nuclear Hardness Critical Feature:

Nonhardened

Style Designator:

Round flush mtg

Fsc Application Data:

Test set, electronic equipment

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A310a0