

View Online at <https://aerobasegroup.com/nsn/6625-00-989-0055>

Circuit Current For Which Designed:

Dc

Overall Length:

3.455 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

3.375 inches

Center To Center Distance Between Mounting Facilities Parallel To Width:

3.375 inches

Overall Height:

4.422 inches

Overall Width:

4.422 inches

Scale Division Quantity:

32 single indicator single range

Mounting Stud Length:

1.500 inches

Environmental Protection:

Shock resistant

Furnished Items And Quantity:

Resistance spool 1; mtg hdw 4; term. Hdw 2

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Four hole/stud rectangular/square

Sensitivity Rating:

100.0 millivolts

Dial Scale Marking Color:

Black single indicator single range

Accuracy In Percent:

-1.5/+1.5 at full scale single indicator single range

Meter Depth Behind Mounting Flange:

2.815 inches

Meter Body Diameter Behind Mounting Flange:

3.960 inches

Movement Type:

Moving coil, permanent magnet

Background Color:

White single indicator single range

Pointer Color:

Black single indicator single range

Power Source:

External

Mounting Facility Type And Quantity:

4 threaded stud

Scale Graduation Type:

Linear single indicator single range

Measurement Range:

-80.0/+80.0 amperes, dc single indicator single range

Mounting Stud Diameter:

0.250 inches

Scale Selection Method:

Terminal

Features Provided:

Zero adjuster

Movement Suspension Method:

Jewel pivot base

Circuit Attachment Method And Quantity:

2 threaded stud

Special Features:

Calibrated for use w/100 mv external shunt

Material:

Plastic

Nuclear Hardness Critical Feature:

Nonhardened

Style Designator:

Rectangular flush mtg

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A310a0