## NSN 6625-00-990-2475

Multiple Scale Meter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6625-00-990-2475

## **Circuit Current For Which Designed:** Dc **Overall Length:** 2.812 inches Center To Center Distance Between Mounting Facilities Parallel To Length: 1.875 inches Center To Center Distance Between Mounting Facilities Parallel To Width: 1.875 inches **Overall Height:** 2.375 inches **Overall Width:** 2.375 inches **Scale Division Quantity:** 40 single indicator 2nd range **Mounting Stud Length:** Between 0.475 inches and 0.625 inches **Environmental Protection:** Dust resistant and humidity resistant and water resistant **Furnished Items And Quantity:** Mtg hdw 4; term. Hdw 2 **Indicator Type:** Dial w/pointer Installation Design: Panel **Mounting Arrangement Style:** Four hole/stud rectangular/square Sensitivity Rating: 1.0 milliamperes **Dial Scale Marking Color:** Black single indicator all ranges Accuracy In Percent: -2.0/+2.0 at full scale single indicator all ranges Meter Depth Behind Mounting Flange: 1.781 inches Meter Body Diameter Behind Mounting Flange: 2.219 inches

**Movement Type:** 

Moving coil, permanent magnet

## **Background Color:**

White single indicator all ranges

**Pointer Color:** 

Black single indicator all ranges

## NSN 6625-00-990-2475

Multiple Scale Meter - Page 2 of 2



Power Sou	rce:
External	
Mounting F	acility Type And Quantity:
4 threaded	stud
Scale Grad	uation Type:
Nonlinear s	ngle indicator 1st range
Measurem	ent Range:
+0.0/+60.0	decibels single indicator 1st range
Mounting S	Stud Diameter:
0.112 inche	S
Scale Sele	ction Method:
Terminal	
Features P	rovided:
Magnetic sh	ield and shatterproof glass and zero adjuster
Movement	Suspension Method:
Jewel pivot	base
Circuit Atta	chment Method And Quantity:
2 solder lug	and 2 threaded stud
Special Ma	rkings:
Left termina	I shall be marked positive
Material:	
Plastic	
Nuclear Ha	rdness Critical Feature:
Nonharden	ed
Surface Tre	eatment:
Enamel	
Style Desig	inator:
Rectangula	r flush mtg
Supplemer	itary Features:
Meter resist	ance: 50 ohms plus or minus 20 percent; number 47 miniature bayonet base bulb with lugs included in mounting hardware
Fsc Applic	ation Data:
Test set, ele	ect. Equip.
Shelf Life:	
N/a	
Unit Of Me	asure:
Demilitariz	ation:
No	
Fiig:	
A310a0	