

View Online at <https://aerobasegroup.com/nsn/6625-00-993-0882>

Overall Length:

24.000 inches

Overall Height:

16.000 inches

Overall Width:

13.000 inches

Current Type:

Ac

Frequency Rating:

Between 50.0 hertz and 400.0 hertz

Accessory Components And Quantity:

Adapter, post 1, cord, power 1, filter, light 1, lead, test 1, probe, attenuation 2

Voltage Rating:

125.0 volts

Beam Quantity:

1

Screen Size:

5 in.

Sweep Circuits:

Included

Generator Driven Feature:

Not included

Sweep Circuit Type:

Vertical and horizontal

Sweep Frequency Range:

+84.000/+100000.000 hertz

Single Trigger Sweep Duration:

1.0 milliseconds

Trigger Sweep Voltage Amplitude Rating:

100.0 volts

Trigger Sweep Polarity Switch:

Included

Expanded Sweep:

Not provided

Amplifier Deflection Sensitivity Provision:

Provided

Vertical Deflection Sensitivity Voltage Rating:

500.0 microvolts rms per inch

Horizontal Deflection Sensitivity Voltage Rating:

200.0 millivolts any acceptable outside diameter

Input Intensity Modulation Feature:

Not provided

Plate Direct Connection Deflection Sensitivity Provision:

Provided

Direct Connection Vertical Deflection Sensitivity Voltage Rating:

7.0 volts any acceptable outside diameter

Direct Connection Horizontal Deflection Sensitivity Voltage Rating:

30.0 volts rms per inch

Frequency Response Rating:

Provided

X-axis Frequency Response Rating:

Between 5.0 hertz and 240000.0 hertz

Y-axis Frequency Response Rating:

Between 0.000005 megahertz and 30.000000 megahertz

Amplifier Input Impedance Rating Provision:

Provided

X-axis Input Impedance Rating:

1.0 megohms

Y-axis Input Impedance Rating:

1.0 megohms

Z-axis Input Impedance Rating:

1.0 megohms

Calibrated Screen Scale:

Not included

Trace Storage Tube:

Not included

Camera Recording Device Accommodation:

Not provided

Phase:

Single

Reference Data And Literature:

To 33a1-13-229-1

Fsc Application Data:

Oscilloscope, except specially designed

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

T320-g